Polycraft Poly-Smash Part B

Page: 1

Compilation date: 23/09/2016

Revision date: 21/08/2018

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Polycraft Poly-Smash Part B

Product code: QL7383

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b:

Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13:

formulation of preparations* and articles (multistage and/or significant contact)

Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: MB Fibreglass

Unit 17 & 20 Abbey Business Park

Mill Road, Newtownabbey

Co.Antrim BT36 7EE

Tel: 02890 861992

Email: sales@mbfg.co.uk

Polycraft Poly-Smash Part B

Page: 2

1.4. Emergency telephone number

Emergency tel: 02890 861992

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Acute Tox. 2: H330; Aquatic Chronic 3: H412; Resp. Sens. 1: H334; Skin

Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties if

inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H330: Fatal if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS06: Skull and crossbones

GHS08: Health hazard





Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: Wear respiratory protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

Polycraft Poly-Smash Part B

Page: 3

3.2. Mixtures

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE) - REACH registered number(s): 01-2119457437-31

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-863-2	5124-30-1	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315;	>50%
			Resp. Sens. 1: H334; Skin Sens. 1: H317	

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE - REACH registered number(s): 01-2119490408-31

223-861-6	4098-71-9	-	Acute Tox. 3: H331; Eye Irrit. 2: H319;	1-25%
			STOT SE 3: H335; Skin Irrit. 2: H315;	
			Resp. Sens. 1: H334; Skin Sens. 1:	
			H317; Aquatic Chronic 2: H411	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion

of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

Polycraft Poly-Smash Part B

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes

or gas. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage

container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in

the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Polycraft Poly-Smash Part B

Page: 5

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

UK	0.02 mg/m3	0.07 mg/m3	-	-
----	------------	------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Type	Exposure	Value	Population	Effect
DNEL	Dermal	0.6 mg/m3	Workers	Local
PNEC	Fresh water	> 0.005 mg/l	-	-
PNEC	Marine water	> 0.0005 mg/l	-	-
PNEC	Soil (agricultural)	> 4.3 mg/kg	-	-
DNEL	Inhalation	0.3 mg/m3	Workers	Local
PNEC	Microorganisms in sewage treatment	1.91 mg/l	-	-
PNEC	Fresh water sediments	> 21.75 mg/kg dry we	-	-
PNEC	Marine sediments	> 2.175 mg/kg dry we	-	-

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	0.0453 mg/m3	Workers	Long term - Local
PNEC	Fresh water	0.06 mg/l	-	-
PNEC	Marine water	0.006 mg/l	-	-
PNEC	Fresh water sediments	218.92 mg/kg (dw)	-	-
PNEC	Marine sediments	21.89 mg/kg (dw)	-	-
PNEC	Soil (agricultural)	44.01 mg/kg (dw)	-	-
PNEC	Microorganisms in sewage	10.6 mg/l	-	-
	treatment			

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be used in handling.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Polycraft Poly-Smash Part B

Page: 6

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Odourless

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: Non-viscous

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 1.04 - 1.09 pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Polycraft Poly-Smash Part B

Page: 7

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

DERMAL	RAT	LD50	> 7000	mg/kg
DUST/MIST	RAT	4H LC50	0.33	mg/l
ORL	RAT	LD50	18200	mg/kg

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

DUST/MIST	RAT	4H LC50	0.031	mg/l
ORL	MUS	LDLO	> 3645	mg/kg
ORL	RAT	LD50	4814	mg/kg
SKN	RAT	LD50	>7000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 2)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion

of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

Polycraft Poly-Smash Part B

Page: 8

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Daphnia magna	EC0 (48h)	>= 8.3	mg/l
Scenedesmus Subspicatus	EC10 (72h)	1.2	mg/l
Scenedesmus Subspicatus	ErC50 (72h)	> 5	mg/l
ZEBRAFISH (Brachydanio rerio)	LC0 (96h)	>= 8.1	mg/l

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

CARP (Cyprinus carpio)	96H LC50	>208	mg/l
Daphnia magna	48H EC50	27	mg/l
GREEN ALGAE (Desmodesmus subspicatus)	72H ErC50	>70	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>72	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 05 01

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2206

14.2. UN proper shipping name

Shipping name: ISOCYANATES, TOXIC, N.O.S.

(Aliphatic Isocyanates)

Polycraft Poly-Smash Part B

Page: 9

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H330: Fatal if inhaled.

H331: Toxic if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.