

#### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 1

Compilation date: 01/09/2014

**Revision date:** 24/04/2015

Revision No: 2

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: FARECLA PROFILE PREMIUM LIQUID COMPOUND

Product code: PRL101, 106, 201

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC31: Polishes and wax blends.

### 1.3. Details of the supplier of the safety data sheet

Company name: Farecla Products Limited

Broadmeads

Ware

Hertfordshire SG12 9HS

UK

Tel: +44 (0)1920 465041

Fax: +44 (0)1920 466557

Email: technical@farecla.com

## 1.4. Emergency telephone number

Emergency tel: +44 (0)1920 465041

(office hours only)

### Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Contains pine oil, 1,2-benzisothiazolin-3-one. May produce an allergic reaction. Harmful

to aquatic life with long lasting effects.

#### 2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains pine oil, 1,2-benzisothiazolin-3-one. May produce an allergic

reaction.

H412: Harmful to aquatic life with long lasting effects.

Precautionary statements: P273: Avoid release to the environment.

P501: Dispose of contents/container to local specialized disposal company.

### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 2

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

ALUMINIUM OXIDE - REACH registered number(s): 01-2119529248-35-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-691-6	1344-28-1	Substance with a Community	-	10-30%
		workplace exposure limit.		

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number (s): 01-2119456620-43-XXXX

926-141-6	-	- Asp. Tox. 1: H304; -:	EUH066 10-30%
-----------	---	-------------------------	---------------

WHITE MINERAL OIL 68CPS - REACH registered number(s): 01-2119487078-27-XXXX

232-455-8	8042-47-5	Substance with a Community	-	1-10%
		workplace exposure limit.		

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) - REACH registered number(s): 01-2119473977-17-XXXX

919-164-8	-	-	Asp. Tox. 1: H304; Aquatic Chronic 3:	1-10%
			H412	

HYDROCARBONS, C10, AROMATICS <1% NAPTHALENE - REACH registered number(s): 01-2119463583-34-XXXX

918-811-1	-	-	STOT SE 3: H335; STOT SE 3: H336;	1-10%
			Asp. Tox. 1: H304; Aquatic Chronic 2:	
			H411	

WHITE MINERAL OIL (PETROLEUM) - REACH registered number(s): 01-2119487078-27-XXXX

232-455-8	8042-47-5	Substance with a Community	Asp. Tox. 1: H304	1-10%
		workplace exposure limit.		

HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-2119457735-29-0003

919-029-3	-	Substance with a Community	Asp. Tox. 1: H304; -: EUH066	1-10%
		workplace exposure limit.		

PINE OIL - REACH registered number(s): 01-2119553062-49-0005

232-268-1	8000-41-7	-	Flam. Liq. 3: H226; Skin Irrit. 2: H315;	<1%
			Skin Sens. 1: H317; Aquatic Chronic 2:	
			H411; Eye Irrit. 2: H319; Asp. Tox. 1:	
			H304	

### Section 4: First aid measures

#### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 3

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Move to fresh air.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 4

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Not applicable.

### 7.3. Specific end use(s)

Specific end use(s): PC31: Polishes and wax blends.

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Hazardous ingredients:**

# ALUMINIUM OXIDE

Workplace e	exposure	limits:
-------------	----------	---------

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	5mg/m3	-

### HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

EU	1200mg/m3, 165ppm	-	-	-
----	-------------------	---	---	---

### WHITE MINERAL OIL 68CPS

EU	5 mg/m3	-	-	-
----	---------	---	---	---

### HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

FII	10ppm, 50mg/m3	_	_	_
	roppin, comg/inc			

### **HYDROCARBONS, C10, AROMATICS <1% NAPTHALENE**

EU	10 ppm, 50 mg/m3	-	-	-
----	------------------	---	---	---

## WHITE MINERAL OIL (PETROLEUM)

EU	5 mg/m3	-	-	-
----	---------	---	---	---

### HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

EU	5 mg/m	-	-	-

# PINE OIL

EII	25 ppm. 140 mg/m3	50 ppm, 300 mg/m3	_	_
	23 ppin, 140 mg/m3	Jo ppin, Joo mg/ma	_	_

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

#### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 5

Respiratory protection: When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community

environmental legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid Colour: White

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Slightly soluble

Also soluble in: No data available

Viscosity: Viscous

Kinematic viscosity: 20,000

Viscosity test method: Brookfield @ 20degC

Boiling point/range°C: Not Available Melting point/range°C: Not Available

Flammability limits %: lower: Not Available upper: Not Available

Flash point°C: >93 Part.coeff. n-octanol/water: Not Available

Autoflammability°C: Not Available Vapour pressure: Not Available

Relative density: 1.150 pH: 7 - 8

VOC g/l: 266

#### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 6

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

# 11.1. Information on toxicological effects

### **Hazardous ingredients:**

### **ALUMINIUM OXIDE**

DUST/MIST	RAT	LC50	7.6	mg/l
ORAL	RAT	LD50	> 2000	mg/kg

## HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

DERMAL	RBT	LD50	> 5000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg
VAPOURS	RAT	8H LC50	> 5000	mg/l

### WHITE MINERAL OIL 68CPS

IHL	RAT	LC50	5200	mg/m3
ORL	RAT	LD50	5000	mg/kg
SKN	RBT	LD50	2000	mg/kg

### HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LD50	>13.1	mg/l

### HYDROCARBONS, C10, AROMATICS <1% NAPTHALENE

DERMAL	RBT	LD50	>2000	mg/kg
GASES	RAT	4H LC50	>4688	mg/l
ORAL	RAT	LD50	>5000	mg/kg

## HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

DERMAL	RBT	LD50	>3160	mg/kg
--------	-----	------	-------	-------

### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 7

ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5266	mg/l

#### **PINE OIL**

DERMAL	RBT	LD50	> 2000	mg/kg
ORAL	RAT	LD50	> 2000	mg/kg
VAPOURS	RAT	4H LC50	4.76	mg/l

Toxicity values: No data available.

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

Other information: Not applicable.

## Section 12: Ecological information

## 12.1. Toxicity

## **Hazardous ingredients:**

### **ALUMINIUM OXIDE**

Daphnia magna	48H EC50	> 100	mg/l
GREEN ALGA (Selenastrum capricornutum)	48H EC50	> 100	mg/l
Salmo trutta	96H LC50	> 100	mg/l

## HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Daphnia magna	48H EC50	1000	mg/l
Pseudokirchneriella subcapitata	72H ErC50	1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1000	mg/l

## HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

ALGAE	72H EL50	50 - 100	mg/l
Daphnia magna	48H EL50	10 - 22	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LL50	10 - 100	mg/l

### HYDROCARBONS, C10, AROMATICS <1% NAPTHALENE

ALGAE	72H ErC50	11	ma/l
ALGAE	/2H ErC50		1119/1

#### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 8

Daphnia magna	48H EC50	3 - 10	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	2 - 5	mg/l

### HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

FISH	96H LC50	1028	mg/l
Invertebrate	48H EC50	>3000	mg/l
MARINE ALGAE (Skeletonema costatum)	72H ErC50	3198	mg/l

### **PINE OIL**

ALGAE	72H ErC50	68	mg/l
Daphnia magna	48H EC50	73	mg/l
FISH	96H LC50	>62	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable. More than 80% biodegradable according to OECD 301 (calculated).

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Harmful to aquatic life with long lasting effects.

# Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Waste code number: 08 04 12

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

## **Section 15: Regulatory information**

#### FARECLA PROFILE PREMIUM LIQUID COMPOUND

Page: 9

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains < name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.