



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SD 5503
Product code : 872.
Hardener for epoxy resin
UFI : F2U5-K0QF-T003-7XYM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Hardener
Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name : SICOMIN Composites.
Address : 31 avenue de la Lardiere - BP 23.13161.Chateauneuf les Martigues.France.
Telephone : +33 (0)4 42 42 30 20. Fax : +33 (0)4 42 81 29 29.
e-mail: composites@sicomin.com
Site web : <http://www.sicomin.com>
AUSTRALIAN Importer : Lavender CE Pty Ltd - 108 Westgate Street - Wacol, Qld, 4076 AUSTRALIA / M: 0409 892 032 / Ph: +61 7 3255 6924 /
Fax: +61 7 3255 6923 / Web: www.lavender-ce.com / Email: sheading@lavender-ce.com

1.4. Emergency telephone number : .

Association/Organisation : INRS / ORFILA tél: +33(0)1.45.42.59.59 - (FRANCE) .

Other emergency numbers

Health and Safety Executive (HSE) Chemicals Regulation Directorate - Telephone: +44 151 951 3317 - USA : +1/ 800/ 424.9300 -
AUSTRALIA : Emergency Poison Advice : 131 126

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).
Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).
Skin corrosion, Category 1B (Skin Corr. 1B, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Reproductive toxicity, Category 1B (Repr. 1B, H360F).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

GHS07

GHS08

GHS09

Signal Word :

DANGER

Product identifiers :

EC 500-105-6

EC 220-666-8

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE

EC 216-032-5	META XYLENE DIAMINE
EC 201-245-8	BISPHENOL A
EC 268-626-9	POLYETHYLENEDIAMINES
601-053-00-8	4-NONYLPHENOL, BRANCHED
CAS 1293368-66-7	FORMALDEHYDE, POLYMERS WITH DIETHYLENEDIAMINE AND STYRENATED PHENOL
EC 223-775-9	3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE
EC 216-032-5	META XYLENEDIAMINE
EC 262-975-0	PHENOL, STYRENATED

Additional labeling :

For professional use only.

Hazard statements :

H302 + H312	Harmful if swallowed or in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...

Precautionary statements - Response :

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER/doctor/...
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.

Other information :

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 39423-51-3 EC: 500-105-6 REACH: 01-2119556886-20-XXXX PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411		25 \leq x % < 50
CAS: 2855-13-2 EC: 220-666-8 REACH: 01-2119514687-32-XXXX 3-AMINOMETHYL-3,5,5-TRIMETHYL-C YCLOHEXYLAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		25 \leq x % < 50
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50-XXXX META XYLENE DIAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Eye Dam. 1, H318	[1]	10 \leq x % < 25

	Acute Tox. 4, H332 Aquatic Chronic 3, H412		
CAS: 80-05-7 EC: 201-245-8 REACH: 01-2119457856-23-XXXX BISPHENOL A	GHS05, GHS09, GHS07, GHS08 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335 Repr. 1B, H360F Aquatic Chronic 2, H411	[1] [2] [6]	2.5 <= x % < 10
CAS: 68131-73-7 EC: 268-626-9 REACH: 01-2119485823-28-XXXX POLYETHYLENEDIAMINES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		2.5 <= x % < 10
INDEX: 601-053-00-8 CAS: 84852-15-3 EC: 284-325-5 REACH: 01-2119510715-45-XXXX 4-NONYLPHENOL, BRANCHED	GHS08, GHS05, GHS07, GHS09 Dgr Repr. 2, H361fd Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[2] [6]	1 <= x % < 2.5
CAS: 1293368-66-7 FORMALDEHYDE, POLYMERS WITH DIETHYLENEDIAMINE AND STYRENATED PHENOL	GHS05, GHS07 Dgr Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318		1 <= x % < 2.5
CAS: 4067-16-7 EC: 223-775-9 REACH: 01-219485826-22-XXXX 3,6,9,12-TETRA-AZATETRADECAMETH YLENEDIAMINE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		1 <= x % < 2.5
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50-XXXX META XYLENEDIAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 4, H332	[1]	0 <= x % < 1
CAS: 61788-44-1 EC: 262-975-0 REACH: 01-2119980970-27-XXXX PHENOL, STYRENATED	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411		0 <= x % < 1

CAS: 69-72-7 EC: 200-712-3 REACH: 01-2119486984-17-XXXX SALICYLIC ACID	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d	[2]	0 <= x % < 1
---	--	-----	--------------

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

[6] Substances of very high concern (SVHC).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.

If breathing is irregular or stopped, that qualified personnel provide artificial respiration and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- foam

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep away from food and drink, including those for animals.

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Recommended application area: wood system

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
80-05-7	2	-	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1477-55-0			0.1 mg/m3	Skin	
1477-55-0			0.1 mg/m3	Skin	

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
80-05-7		5 mg/m ³		1(1 TM)

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1477-55-0	-	-	-	0.1	-	-
80-05-7		2	-	-	R1B	
1477-55-0	-	-	-	0.1	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-05-7	- ppm 10 mg/m ³	- ppm - mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

META XYLENEDIAMINE (CAS: 1477-55-0)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Long term systemic effects.
0.33 mg/kg de poids corporel/jourExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
1.2 mg de substance/m3Exposure method:
Potential health effects:
DNEL :Inhalation.
Long term local effects.
0.2 mg de substance/m3

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Long term systemic effects.
0.91 mg/kg de poids corporel/jourExposure method:
Potential health effects:
DNEL :Dermal contact.
Long term local effects.
0.044 mg de substance/cm2Exposure method:
Potential health effects:
DNEL :Inhalation.
Short term systemic effects.
8550 mg de substance/m3Exposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
1.59 mg de substance/m3**Final use:**Exposure method:
Potential health effects:
DNEL :**Consumers.**Ingestion.
Short term systemic effects.
32 mg/kg de poids corporel/jourExposure method:
Potential health effects:
DNEL :Ingestion.
Long term systemic effects.
0.65 mg/kg de poids corporel/jourExposure method:
Potential health effects:Dermal contact.
Short term systemic effects.

DNEL : 13 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Short term local effects.
DNEL : 1.59 mg de substance/cm2

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.4 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.68 mg de substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 2542 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 0.46 mg de substance/m3

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Final use:

Workers.

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.91 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.44 mg de substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 8550 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1.59 mg de substance/m3

Final use:

Consumers.

Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 32 mg/kg de poids corporel/jour

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.65 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 13 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Short term local effects.
DNEL : 1.59 mg de substance/cm2

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.4 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.68 mg de substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 2542 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 0.46 mg de substance/m3

BISPHENOL A (CAS: 80-05-7)**Final use:****Workers.**

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 0.031 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.031 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 2 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 2 mg de substance/m3

Final use:**Man exposed via the environment.**

Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 0.004 mg/kg de poids corporel/jour

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.004 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 0.002 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.002 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Short term local effects.
DNEL : 1 mg de substance/m3

META XYLENE DIAMINE (CAS: 1477-55-0)**Final use:****Workers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.

DNEL : 0.33 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1.2 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 0.2 mg de substance/m3

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Final use: **Workers.**

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 20.1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Short term local effects.
DNEL : 20.1 mg de substance/m3

Final use: **Man exposed via the environment.**

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.526 mg/kg de poids corporel/jour

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Final use: **Workers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 1.6 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 14 mg de substance/m3

Final use: **Consumers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.8 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 3.48 mg de substance/m3

Predicted no effect concentration (PNEC):

META XYLENEDIAMINE (CAS: 1477-55-0)

Environmental compartment: Soil.
PNEC : 0.045 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.094 mg/l

Environmental compartment: Sea water.
PNEC : 0.009 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.152 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.43 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.043 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10 mg/l

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Environmental compartment: Soil.
PNEC : 0.18 mg/kg

Environmental compartment: Fresh water.
PNEC : 2.5 µg/l

Environmental compartment: Sea water.
PNEC : 2.5 µg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.22 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.14 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 1.64 mg/l

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Environmental compartment: Soil.
PNEC : 10 mg/kg

Environmental compartment: Fresh water.
PNEC : 1.6 µg/l

Environmental compartment: Sea water.
PNEC : 1.6 µg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.14 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.14 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 3.19 mg/l

BISPHENOL A (CAS: 80-05-7)

Environmental compartment: Soil.
PNEC : 3.7 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.018 mg/l

Environmental compartment: Sea water.
PNEC : 0.018 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 1.2 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.24 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 320 mg/l

META XYLENE DIAMINE (CAS: 1477-55-0)

Environmental compartment: Soil.
PNEC : 0.045 mg/kg

Environmental compartment:	Fresh water.
PNEC :	0.094 mg/l
Environmental compartment:	Sea water.
PNEC :	0.009 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.152 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.43 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.043 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	10 mg/l

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Environmental compartment:	Soil.
PNEC :	1.121 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.06 mg/l
Environmental compartment:	Sea water.
PNEC :	0.006 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.23 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	5.784 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.578 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	3.18 mg/l

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Environmental compartment:	Soil.
PNEC :	0.002 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.0044 mg/l
Environmental compartment:	Sea water.
PNEC :	0.00044 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.044 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.02 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.002 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	10 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

Mask with filter type A, B, E, K, P

Attention! If the protection group is insufficient.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Fluid liquid.
Color:	yellow

Important health, safety and environmental information

pH :	Not stated.
	Slightly basic.
Boiling point/boiling range :	Not relevant.
Flash Point Interval :	FP > 100°C.
Vapour pressure (50°C) :	Not relevant.
Density :	1.06 ± 0.02 @ 20°C
Water solubility :	Soluble.
Viscosity :	117.5 ± 22.5 mPa.s @ 25°C
Melting point/melting range :	Not relevant.

Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.
Index of refraction :	1.5045 ± 0.002 @ 25 °C
% VOC :	0

9.2. Other information

Miscibility	Alcohols, aromatic solvents
-------------	-----------------------------

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- humidity

10.5. Incompatible materials

Keep away from :

- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Harmful if swallowed.

Harmful in contact with skin.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

Presumed human reproductive toxicant.

May damage fertility.

11.1.1. Substances**Acute toxicity :**

SALICYLIC ACID (CAS: 69-72-7)

Oral route :

LD50 = 891 mg/kg

Species : Rat

OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

PHENOL, STYRENATED (CAS: 61788-44-1)

Oral route :

LD50 > 2000 mg/kg

Species : Rat

OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode de la classe de toxicité aiguë)

Dermal route :

LD50 > 2000 mg/kg

Species : Rat

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (n/a) :

LC50 = 4.9 mg/l

OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

META XYLENEDIAMINE (CAS: 1477-55-0)

Oral route :	LD50 = 1180 mg/kg Species : Mouse OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 3100 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 = 2.4 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation) Duration of exposure : 4 h
3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)	
Oral route :	LD50 = 1600 mg/kg Species : Rat
Dermal route :	LD50 = 1465.4 mg/kg Species : Rabbit OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)	
Oral route :	LD50 = 1716.2 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 = 1465.4 mg/kg Species : Rabbit OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
BISPHENOL A (CAS: 80-05-7)	
Oral route :	LD50 = 3250 mg/kg Species : Rat
Dermal route :	LD50 = 3000 mg/kg Species : Rabbit
META XYLENE DIAMINE (CAS: 1477-55-0)	
Oral route :	LD50 = 1180 mg/kg Species : Mouse OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 3100 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 = 1.34 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation) Duration of exposure : 4 h
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)	
Oral route :	LD50 = 1030 mg/kg Species : Rat
Dermal route :	LD50 > 2000 mg/kg Species : Rat OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
Inhalation route (n/a) :	LC50 > 5.01 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)
PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)	
Oral route :	LD50 = 550 mg/kg Species : Rat

OCDE Ligne directrice 425 (Toxicité aiguë par voie orale - Méthode de l'ajustement des doses)

Dermal route :

LD50 > 1000 mg/kg

Species : Rat

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Skin corrosion/skin irritation :

PHENOL, STYRENATED (CAS: 61788-44-1)

Effect observed : Irritation globale

Species : Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

META XYLENEDIAMINE (CAS: 1477-55-0)

Corrosivity :

Causes severe skin burns.

META XYLENE DIAMINE (CAS: 1477-55-0)

Corrosivity :

Causes severe skin burns.

Species : Rat

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Species : Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

Species : Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

Serious damage to eyes/eye irritation :

PHENOL, STYRENATED (CAS: 61788-44-1)

Species : Rabbit

Respiratory or skin sensitisation :

BISPHENOL A (CAS: 80-05-7)

Species : Guinea pig

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Species : Rabbit

OCDE Ligne directrice 406 (Sensibilisation de la peau)

Germ cell mutagenicity :

META XYLENEDIAMINE (CAS: 1477-55-0)

Ames test (in vitro) :

Negative.

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Mutagenesis (in vivo) :

Negative.

OCDE Ligne directrice 474 (Le test de micronoyaux sur les érythrocytes de mammifères)

OCDE Ligne directrice 471 (Essai de mutation réverse sur des bactéries)

Ames test (in vitro) :

Negative.

With or without metabolic activation.

PHENOL, STYRENATED (CAS: 61788-44-1)

No mutagenic effect.

Mutagenesis (in vivo) :

Negative.

OCDE Ligne directrice 474 (Le test de micronoyaux sur les érythrocytes de mammifères)

OCDE Ligne directrice 471 (Essai de mutation réverse sur des bactéries)

Ames test (in vitro) :

Negative.

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

No mutagenic effect.

Mutagenesis (in vivo) : Negative.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

No mutagenic effect.

Mutagenesis (in vivo) : Negative.

OCDE Ligne directrice 474 (Le test de micronoyaux sur les érythrocytes de mammifères)

META XYLENE DIAMINE (CAS: 1477-55-0)

No mutagenic effect.

Reproductive toxicant :

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

OCDE Ligne directrice 414 (Étude de la toxicité pour le développement prénatal)

BISPHENOL A (CAS: 80-05-7)

May damage fertility.

META XYLENE DIAMINE (CAS: 1477-55-0)

No toxic effect for reproduction

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Study on development :

Species : Rat

OCDE Ligne directrice 421 (Essai de dépistage de la toxicité pour la reproduction et le développement)

Specific target organ systemic toxicity - repeated exposure :

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Dermal route :

C > 160 mg/kg poids corporel/jour

Duration of exposure : 90 jours

OCDE Ligne directrice 411 (Toxicité cutanée subchronique: 90 jours)

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Species : Rat

META XYLENE DIAMINE (CAS: 1477-55-0)

Oral route :

C = 600 mg/kg poids corporel/jour

Species : Rat

Duration of exposure : 28 jours

OCDE Ligne directrice 407 (Toxicité orale à doses répétées - pendant 28 jours sur les rongeurs)

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Fish toxicity : Duration of exposure : 96 h

Crustacean toxicity : Duration of exposure : 48 h

NOEC = 0.8 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours

Algae toxicity :

ECr50 = 0.7 mg/l
Factor M = 1
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

NOEC = 0.25 mg/l
Duration of exposure : 72 h

META XYLENE DIAMINE (CAS: 1477-55-0)

Fish toxicity :

LC50 = 87.6 mg/l
Species : Oryzias latipes
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :

EC50 = 15.2 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

EC50 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours
OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)

NOEC = 4.7 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours
OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)

Algae toxicity :

ECr50 = 33.3 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

NOEC = 10.5 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Fish toxicity :

LC50 = 110 mg/l
Species : Leuciscus idus
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 23 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

NOEC = 3 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :

ECr50 > 50 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h

NOEC = 1.5 mg/l
Species : Desmodesmus subspicatus

Duration of exposure : 72 h

Autres lignes directrices

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Fish toxicity :

LC50 > 100 mg/l

Species : *Oncorhynchus mykiss*

Duration of exposure : 96 h

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :

EC50 = 13 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

OCDE Ligne directrice 202 (*Daphnia* sp., essai d'immobilisation immédiate)

Algae toxicity :

ECr50 = 4.4 mg/l

Species : *Selenastrum capricornutum*

Duration of exposure : 72 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

PHENOL, STYRENATED (CAS: 61788-44-1)

Fish toxicity :

LC50 = 14.8 mg/l

Duration of exposure : 96 h

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :

EC50 <= 10 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

OCDE Ligne directrice 202 (*Daphnia* sp., essai d'immobilisation immédiate)

NOEC = 0.115 mg/l

Duration of exposure : 21 jours

OCDE Ligne directrice 211 (*Daphnia magna*, essai de reproduction)

Algae toxicity :

ECr50 = 3.14 mg/l

Duration of exposure : 72 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

META XYLENEDIAMINE (CAS: 1477-55-0)

Fish toxicity :

LC50 = 87.6 mg/l

Species : *Oryzias latipes*

Duration of exposure : 96 h

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

EC50 mg/l

Duration of exposure : 21 jours

Crustacean toxicity :

EC50 = 15.2 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

OCDE Ligne directrice 202 (*Daphnia* sp., essai d'immobilisation immédiate)

EC50 mg/l

Species : *Daphnia magna*

Duration of exposure : 21 jours

OCDE Ligne directrice 211 (*Daphnia magna*, essai de reproduction)

NOEC = 4.7 mg/l

Species : *Daphnia magna*

Duration of exposure : 21 jours

OCDE Ligne directrice 211 (*Daphnia magna*, essai de reproduction)

Algae toxicity :

ECr50 = 33.3 mg/l

Species : *Pseudokirchnerella subcapitata*

Duration of exposure : 72 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

NOEC = 10.5 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

Aquatic plant toxicity :

Autres lignes directrices

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Fish toxicity :

LC50 = 100 mg/l

Species : Poecilia reticulata

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 2.2 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity :

ECr50 = 0.23 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

BISPHENOL A (CAS: 80-05-7)

Fish toxicity :

LC50 = 4.6 mg/l

Species : Pimephales promelas

Duration of exposure : 96 h

NOEC = 0.016 mg/l

Species : Others

Crustacean toxicity :

EC50 = 7.75 mg/l

Species : Others

Duration of exposure : 48 h

NOEC = 1.8 mg/l

Algae toxicity :

ECr50 = 2.73 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 96 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

PHENOL, STYRENATED (CAS: 61788-44-1)

Biodegradability :

Non-rapidly degradable.

META XYLENEDIAMINE (CAS: 1477-55-0)

Biodegradability :

Non-rapidly degradable.

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Biodegradability :

Non-rapidly degradable.

BISPHENOL A (CAS: 80-05-7)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

META XYLENE DIAMINE (CAS: 1477-55-0)

Biodegradability :

Non-rapidly degradable.

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Biodegradability : Non-rapidly degradable.

12.3. Bioaccumulative potential**12.3.1. Substances**

PHENOL, STYRENATED (CAS: 61788-44-1)

Octanol/water partition coefficient : log K_{ow} ≤ 5.8
OCDE Ligne directrice 107 (Coefficient de partage (n-octanol/eau): méthode par agitation en flacon)

Bioaccumulation : BCF ≤ 190
OCDE Ligne directrice 305 (Bioconcentration: Essai dynamique chez le poisson)

META XYLENEDIAMINE (CAS: 1477-55-0)

Octanol/water partition coefficient : log K_{ow} = 0.18
OCDE Ligne directrice 107 (Coefficient de partage (n-octanol/eau): méthode par agitation en flacon)

Bioaccumulation : BCF = 2.69

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Octanol/water partition coefficient : log K_{ow} = -3.67

BISPHENOL A (CAS: 80-05-7)

Octanol/water partition coefficient : log K_{ow} = 3.3

Bioaccumulation : BCF = 73

META XYLENE DIAMINE (CAS: 1477-55-0)

Octanol/water partition coefficient : log K_{ow} = 0.18
OCDE Ligne directrice 107 (Coefficient de partage (n-octanol/eau): méthode par agitation en flacon)

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Octanol/water partition coefficient : log K_{ow} = 0.99
OCDE Ligne directrice 107 (Coefficient de partage (n-octanol/eau): méthode par agitation en flacon)

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Octanol/water partition coefficient : log K_{ow} = -1.13

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBWs) :

WGK 3 : Extremely hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 01 08 * other still bottoms and reaction residues

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

2735

14.2. UN proper shipping name

UN2735=AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(propyldynetrimethanol, propoxylated, reaction products with ammonia, 3-aminomethyl-3,5,5-trimethyl-cyclohexylamine)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	8	-	III	5 L	F-A, S-B	223 274	E1	Category A	SGG18 SG35	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	III	852	5 L	856	60 L	A3 A803	E1	
	8	-	III	Y841	1 L	-	-	A3 A803	E1	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

- Container information:

No data available.

Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.

For professional users only.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 3 : Extremely hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique Formula Identifier

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.