

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 1

Compilation date: 15/12/2015

Revision date: 14/07/2020

Revision No: 4

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** Polycraft ClearTop 5 Resin

**Product code:** QL3006

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

### 1.3. Details of the supplier of the safety data sheet

**Company name:** MB Fibreglass  
Unit 17 & 20 Abbey Business Park  
Mill Road  
Newtownabbey  
BT36 7EE  
United Kingdom  
**Tel:** 02890 861992  
**Email:** sales@mbfg.co.uk

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** 02890 861992  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental



**Signal words:** Warning

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label)  
P362+P364: Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 3

BIS [4-(2,3-EPOXYPROPOXY) PHENYL] PROPANE - REACH registered number(s): 01-2119456619-26

EINECS	CAS	PBT / WEL	CLP Classification	Percent
216-823-5	1675-54-3	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	>50%

REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE &[2-((2-[4-(OXIRAN-2-YLMETHOXY)BENZYL] PHENOXY) METHYL)OXIRANE &[2,2'-[METHYLENEBIS(2,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE - REACH registered number(s): 01-2119454392-40

701-263-0	9003-36-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-25%
-----------	-----------	---	---------------------------------------------------------------------	-------

PROPYLENE CARBONATE

203-572-1	108-32-7	-	Eye Irrit. 2: H319	1-25%
-----------	----------	---	--------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 4

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

[cont...]

## SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 5

### Hazardous ingredients:

#### BIS [4-(2,3-EPOXYPROPOXY) PHENYL] PROPANE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	8.33 mg/kg/day	Workers	Systemic
DNEL	Inhalation	12.25 mg/kg/day	Workers	Systemic
DNEL	Dermal	3.571 mg/kg/day	Consumers	Systemic
DNEL	Oral	0.75 mg/kg/day	Consumers	Systemic
PNEC	Fresh water	0.006 mg/l	-	-
PNEC	Marine water	0.0006 mg/l	-	-
PNEC	Microorganisms in sewage treatment	10 mg/l	-	-
PNEC	Fresh water sediments	0.996 mg/kg	-	-
PNEC	Marine sediments	0.0996 mg/kg	-	-
PNEC	Soil (agricultural)	0.196 mg/kg/day	-	-

#### REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE & [2-([4-(OXIRAN-2-YLMETHOXY)BENZOYL]OXY)ETHYL]ACRYLATE

Type	Exposure	Value	Population	Effect
DNEL	Oral	6.25 mg/kg bw/day	General Population	Systemic
DNEL	Dermal	62.5 mg/kg bw/day	General Population	Systemic
DNEL	Dermal	104.15 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	8.7 mg/m3	General Population	Systemic
DNEL	Inhalation	29.39 mg/m3	Workers	Systemic
PNEC	Fresh water	0.003 mg/l	-	-
PNEC	Marine water	0.0003 mg/l	-	-
PNEC	Fresh water sediments	0.294 mg/kg	-	-
PNEC	Marine sediments	0.0294 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	10 mg/l	-	-
PNEC	Soil (agricultural)	0.237 mg/kg soil dw	-	-

#### PROPYLENE CARBONATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	70.53 mg/m3	Workers	Systemic
DNEL	Inhalation	20 mg/m3	Workers	Local
DNEL	Dermal	20 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	17.4 mg/m3	Consumers	Systemic
DNEL	Inhalation	10 mg/m3	Consumers	Local
DNEL	Dermal	10 mg/kg bw/day	Consumers	Systemic

[cont...]

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 6

PNEC	Fresh water	0.9 mg/l	-	-
PNEC	Marine water	0.09 mg/l	-	-
PNEC	Microorganisms in sewage treatment	7400 mg/l	-	-
PNEC	Soil (agricultural)	0.81 mg/kg d.w.	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Perceptible odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** 1900 mPa.s (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.14 - 1.18

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

[cont...]

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 7

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### BIS [4-(2,3-EPOXYPROPOXY) PHENYL] PROPANE

DERMAL	RBT	LD50	23000	mg/kg
IPR	RAT	LD50	2200	mg/kg
ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11300	µl/kg

#### REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE & [2-({ 2-[4-(OXIRAN-2-YLMETHOXY)BENZYL] PHENOXY} METHYL)OXIRANE & [2,2'-[METHYLENEBIS(2,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE

DERMAL	RAT	LD50	> 2000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg

#### PROPYLENE CARBONATE

DERMAL	RBT	LD50	>2000	mg/kg
ORL	RAT	LD50	33520	µl/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

[cont...]

# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 8

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### BIS [4-(2,3-EPOXYPROPOXY) PHENYL] PROPANE

Daphnia magna	48H EC50	1.8	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	11	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	2	mg/l

#### REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE & [2-({ 2-[4-(OXIRAN-2-YLMETHOXY)BE

ALGAE	72H EC50	1.8	mg/l
Daphnia magna	48H EC50	2.55	mg/l
FISH	96H LC50	2.54	mg/l

#### PROPYLENE CARBONATE

Daphnia magna	48H EC50	> 1000	mg/l
FISH (Cyprinus carpio)	96H LC0	> 1000	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H EC50	> 900	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

[cont...]



# SAFETY DATA SHEET

Polycraft Cleartop 5 Resin

Page: 9

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3082

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxy Resin)

### 14.3. Transport hazard class(es)

**Transport class:** 9

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

[cont...]

## **SAFETY DATA SHEET**

Polycraft Cleartop 5 Resin

**Page:** 10

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.