

SAFETY DATA SHEET

Polycraft OptiCast 2000 Part B

Page: 1

Compilation date: 03/08/2017

Revision date: 18/05/2021

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Polycraft OptiCast 2000 Part B

Product code: QL5746

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9b: Fillers, putties, plasters, modelling clay. PC9a: Coatings and paints, thinners, paint removers. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: MB Fibreglass
Unit 17 & 20 Abbey Business Park
Mill Road, Newtownabbey
Co. Antrim
BT36 7EE
United Kingdom
Tel: 02890 861992
Email: sales@mbfg.co.uk

SAFETY DATA SHEET

Polycraft OptiCast 2000 Part B

Page: 2

1.4. Emergency telephone number

Emergency tel: 02890 861992
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Acute Tox. 3: H331; Acute Tox. 4: H312; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335: May cause respiratory irritation.

Hazard pictograms: GHS06: Skull and crossbones
GHS08: Health hazard



Signal words: Danger

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P284: Wear respiratory protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

[cont...]

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

Page: 3

3.2. Mixtures

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE) - REACH registered number(s): 01-2119457437-31

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-863-2	5124-30-1	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	25-50%

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER - REACH registered number(s): 01-2119485796-17

500-060-2	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	25-50%
-----------	------------	---	---	--------

HEXAMETHYLENE-DI-ISOCYANATE - REACH registered number(s): 01-2119457571-37

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	0.05-1%
-----------	----------	---	---	---------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

Polycraft OptiCast 2000 Part B

Page: 4

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

8.1. Control parameters

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

UK	0.02 mg/m3 (as NCO)	0.07 mg/ms (as NCO)	-	-
----	---------------------	---------------------	---	---

HEXAMETHYLENE-DI-ISOCYANATE

UK	0.02 mg/m3	0.07 mg/m3	-	-
----	------------	------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Type	Exposure	Value	Population	Effect
DNEL	Dermal	0.6 mg/m3	Workers	Local
PNEC	Fresh water	> 0.005 mg/l	-	-
PNEC	Marine water	> 0.0005 mg/l	-	-
PNEC	Soil (agricultural)	> 4.3 mg/kg	-	-
DNEL	Inhalation	0.3 mg/m3	Workers	Local
PNEC	Microorganisms in sewage treatment	1.91 mg/l	-	-
PNEC	Fresh water sediments	> 21.75 mg/kg dry we	-	-
PNEC	Marine sediments	> 2.175 mg/kg dry we	-	-

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	0.5 mg/m3	Workers	Systemic
PNEC	Fresh water	0.127 mg/l	-	-
PNEC	Marine water	0.0127 mg/l	-	-
PNEC	Fresh water sediments	266700 mg/kg	-	-
PNEC	Marine sediments	26670 mg/kg	-	-
PNEC	Soil (agricultural)	53182 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	38.3 mg/l	-	-

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

Page: 6

DNEL	Inhalation	0.5 mg/m ³	Workers	Local
------	------------	-----------------------	---------	-------

8.2. Exposure controls

- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.
- Hand protection:** Impermeable gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Impermeable protective clothing.
- Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State:** Liquid
- Colour:** Colourless
- Odour:** Barely perceptible odour
- Evaporation rate:** No data available.
- Oxidising:** No data available.
- Solubility in water:** Reacts with water.
- Viscosity:** 130 mPas (25°C)
- Boiling point/range°C:** No data available.
- Melting point/range°C:** No data available.
- Flammability limits %: lower:** No data available.
- upper:** No data available.
- Flash point°C:** No data available.
- Part.coeff. n-octanol/water:** No data available.
- Autoflammability°C:** No data available.
- Vapour pressure:** No data available.
- Relative density:** 1.08 - 1.13
- pH:** No data available.
- VOC g/l:** No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

[cont...]

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

Page: 7

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

DERMAL	RAT	LD50	> 7000	mg/kg
DUST/MIST	RAT	4H LC50	0.33	mg/l
ORL	RAT	LD50	18200	mg/kg

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

DERMAL	RAT	LD50	>2001	mg/kg
DERMAL	RBT	LD50	>2001	mg/kg
ORAL	RAT	LD50	>2500	mg/kg

HEXAMETHYLENE-DI-ISOCYANATE

IVN	MUS	LD50	5600	µg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	µl/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	DRM	Hazardous: calculated
Acute toxicity (ac. tox. 3)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

[cont...]

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

Page: 8

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Daphnia magna	EC0 (48h)	>= 8.3	mg/l
Scenedesmus Subspicatus	EC10 (72h)	1.2	mg/l
Scenedesmus Subspicatus	ErC50 (72h)	> 5	mg/l
ZEBRAFISH (Brachydanio rerio)	LC0 (96h)	>= 8.1	mg/l

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

Daphnia magna	48H EC50	>100	mg/l
Scenedesmus Subspicatus	72H ErC50	>1000	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>100	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 05 01

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

[cont...]

SAFETY DATA SHEET
Polycraft OptiCast 2000 Part B

Page: 9

14.1. UN number

UN number: UN2206

14.2. UN proper shipping name

Shipping name: ISOCYANATES, TOXIC, N.O.S.
(Aliphatic Isocyanates)

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

[cont...]

SAFETY DATA SHEET

Polycraft OptiCast 2000 Part B

Page: 10

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.